


DATASHEET

Co-Location Rack PRO, 2 x 20U, 800x800 mm, F+R 1-Part
Perforated, RAL9005



General data

19" network cabinet according to DIN 41494

Steel sheet housing with screwed frame, completely pre-assembled, self-ventilated

1, 2, 3 or 4 boxes for individual access

Every box with independent cable ducts left and right for cable entry from top or bottom

Inside front and rear 4 x 19" profiles per box (2 front, 2 rear), galvanised, step-less depth-adjustable

Numbering of height units at the profiles

Front- and rear doors steel, perforated, 1-part

Doors with 1-point turning handle, lockable, incl. profile half-cylinder acc. to DIN 18252 / EN 1303

Profile half-cylinder exchangeable by customer (30/10 mm)

Door stop left and right-sided possible

Detachable side walls with 2 x latch locking (lock equal to door lock)

DATASHEET

Co-Location Rack PRO, 2 x 20U, 800x800 mm, F+R 1-Part Perforated, RAL9005

Side walls optional available perforated

Cabinets stackable side-by-side with and without side wall via baying set PRO-ANR01

Roof and bottom with covered cutouts for cable entry (left/right) and for accommodation of fan unit PRO-LFD02BO.xx

Intermediate bottoms sealed to side walls

Internal earthing of all cabinet parts

Max. load 600 kg

Paint finish RAL7035, light grey / RAL9005, jet black

Protection degree IP20

Included accessories: 1 x set of captive nuts (PU 20 pcs.), 4 x Leveling feet M12, 2 x key

Delivery in transport packaging on disposable pallet

Allgemeine Daten	
With front door	True
Type of ventilation	Passive
With backside door	True
Demountable	True
Surface finishing	With powder coating
With roof plate	True
Type of back door	Steel perforated 1-part
Type of front door	Steel perforated 1-part
Modular spacing	482,6 mm (19 inch)
With sidewall	True
Mounting level	Front and rear
Cabinet Series	PRO
With socket	False
Model	With permanent frame
With earthing	True
Material	steel
Degree of protection (IP)	IP20
Type of profile rail	Crank

Available variants																
ArtNr.	Bezeichnung	Colour	Depth	Front door locking system	Material front door	Material rear door	Max. Load Capacity	Number of height units	Rear door locking system	Width	With vertical cable management	Höhe	RAL-Nummer	Anzahl der Türen	Geeignete Lüfter	Anzahl der Boxen
BAIE-C00-42-80-80NA	Co-Location Rack PRO, 1 x 42U, 800x800 mm, F+R 1-Part Perforated, RAL9005	black	800 mm	One point	Steel	Steel	600 kg	1 x 42 U	One point	800 mm	True	1963 mm	9005	2	PRO-LFD02BT.x	1

DATASHEET

Co-Location Rack PRO, 2 x 20U, 800x800 mm, F+R 1-Part Perforated, RAL9005

BAIE-CO-42-80-80NA	Co-Location Rack PRO, 2 x 20U, 800x800 mm, F+R 1-Part Perforated, RAL9005	black	800 mm	One point	Steel	Steel	600 kg	2 x 20 U	One point	800 mm	True	1963 mm	9005	4	PRO-LFD02BT.x	2
BAIE-CO4-42-80-80NA	Co-Location Rack PRO, 4 x 9U, 800x800 mm, F+R 1-Part Perforated, RAL9005	black	800 mm	One point	Steel	Steel	600 kg	4 x 9 U	One point	800 mm	True	1963 mm	9005	8	PRO-LFD02BT.x	4